

TIPO DE ELECTRODO					
Celulosico		Rutilico		Bajo Hidrogeno	
E6010	NO	E6013	SI	E7018	SI
E6011	SI				

MOD: AXT-202ABV						
	60Hz	30A / 21,2V - 200A / 28V				
		AC220V		AC110V		
IP21S	U ₀ =64V	X	25%	100%	80%	100%
		I ₂	200A	100A	110A	100A
		U ₂	28V	24V	24.4V	24V
	60 Hz	U ₁ =110V U ₁ =220V	I _{1max} =23,5A I _{1max} =42A	I _{1eff} =21A I _{1eff} =21A		

**Bi-voltaje
para Electrodo
y TIG LIFT**
110V-30-110A
220V-30-200A

Soldadora
inversor

Modelo: AXT-202ABV

Voltaje de alimentación: (Bi-voltaje) 110/220V
Consumo: 3,000 \ 7,000Wtts
Frecuencia: 50/60 Hz
Voltaje en vacío: 76V
Rango de Amperaje: 110V 30-110A
220V 30-200A
Rango de voltaje: 24.4/28
Capacidad de electrodo: 3/32" - 5/32"
Medida en mm: 460*270*345
Peso: 10 Kgs

Interruptor: para función TIG LIFT

Ciclo de trabajo:
110V 220V

100%	80%
100A	110A

100%	25%
100A	200A

Para Electrodo
de acero inoxidable
serie 308.

Para Electrodo
de aluminio series
2201, 4043, 5056



Recomendada para:
Trabajos profesionales
e industrial ligero



ANTORCHA TIG
Modelo: AXT-VP-26
Se vende
por separado

